



RHINO C65R

A 6" 5G Android handheld built for enterprise.

Included In This Box

- RHINO C65R
- USB-C to USB-C cable (USB 2.0)
- Charger block
- Quick start guide
- SIM pin



Get Started

Press and hold the power button for 4 seconds until the device turns on and vibrates.

This device may be pre-provisioned by your organization, so the Android setup flow you are used to may be interrupted by the Android zero-touch management prompt.

User Manual

Download the full user manual for this device at rhinomobility.com

Software and Security Updates

Check for the latest software and security updates at rhinomobility.com/software-releases

Customer Support

Online: Go to kb.rhinomobility.com/support
Email: support@rhinomobility.com

Warranty

Your RHINO device is protected by a one (1) year limited liability warranty against manufacturing defects. This does not affect your statutory rights.

Further warranty can be found at kb.rhinomobility.com/support/rhino-warranty

Documents

View all documents for this device at rhinomobility.com/c65r/specifications



CE Statement

1. The adapter shall be installed near the equipment and shall be easily accessible.
2. Do not use the device in the environment at too high or too low temperature, never expose the device under strong sunshine or too wet environment. The operating temperature for the product is 0°C to 40°C (while charging is 35°C).
3. **Caution:** Risk of explosion if battery is replaced by an incorrect type. Dispose of used batteries according to the instructions.
4. The SAR limit of Europe is 2.0 W/kg. This device was tested for typical body-worn operations with the 5mm distance from the body and it complies with RF exposure requirements.

Head: 1.690 W/kg

Body: 1.450 W/kg

Limbs: 3.040 W/kg

5. RF frequency and power

WWAN		
Frequency Band		Maximum output power(dBm)
WCDMA Band I		25.00
WCDMA Band VIII		25.00
LTE B1		24.50
LTE B3		24.50
LTE B7		23.50
LTE B8		24.50
LTE B20		24.50
LTE B28		24.50
LTE B38		24.50
LTE B41		27.00
NR n7		23.50
NR n28		24.50
NR n41		26.00
NR n77		28.00
NR n78		27.00
WLAN		
Standard	Frequency	EIRP Power(dBm)
WIFI 2.4G	2.4~2.4835GHz	17.49
	5.15~5.25GHz	14.98
WIFI 5G	5.725~5.825GHz	13.20
BLUETOOTH		
Bluetooth Version		EIRP Power(dBm)
EDR		9.65
LE		9.98
NFC		
Frequency	13.56MHz	-10.64 dBμA/m at 10m

6. The Wi-Fi function is restricted to indoor use only when operating in the 5150 MHz to 5350 MHz frequency range.

	AT	BE	BG	HR	CY	CZ	DK
	EE	FI	FR	DE	EL	HU	IE
	IT	LV	LT	LU	MT	NL	PL
	PT	RO	SK	SI	ES	SE	UK

7. Prevention of hearing loss:



Prevention of Hearing Loss

To prevent possible hearing damage, do not listen at high volume levels for long periods.

Manufacturer Information

Rhino Mobility LLC
8 The Green, Suite A, Dover, Delaware, 19901, USA

EU Regulatory Conformance

Hereby, Rhino Mobility LLC declares that this device is in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU.

For the declaration of conformity, visit the Web site rhinomobility.com

Manufacturer: Rhino Mobility LLC
8 The Green, Suite A, Dover, Delaware 19901, USA
© 2026 Rhino Mobility™. All rights reserved.
Not intended for consumer use or resale.
C65R-007-RHN-0A-001